




P-6720A



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA

Rua Buri, 149 - Laranjeiras – CAIEIRAS/SP – CEP: 07739-600

11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Clevis Hook for Green Pin Tycan®

Grade 10 clevis hook with safety latch for use with Green Pin Tycan® Chain

- **Material:** alloy steel
- **Safety factor:** MBL equals 4 x WLL and MBL equals 2 x Lashing Capacity
- **Finish:** painted blue
- **Certification:** 2.1 2.2 CE
- **Compatible with:** FCHLIFT1525, FCHLASH1525

for chain size	working load limit	lashing capacity	length	width	width	width outside	width outside	length outside	diameter pin	weight each
mm	t	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
15x25	5	10	110	26	40	62	113	179	16	1.25

In inch

for chain size	working load limit	lashing capacity	length	width	width	width outside	width outside	length outside	diameter pin	weight each
inch	t	t	a inch	b inch	c inch	d inch	e inch	f inch	g inch	lbs
$1^{9/32} \times 1$	5	10	$4 \frac{11}{32}$	1	$1 \frac{9}{16}$	$2 \frac{7}{16}$	$4 \frac{29}{64}$	7	$\frac{5}{8}$	2.75