



## LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA

Rua Buri, 149 - Laranjeiras – CAIEIRAS/SP – CEP: 07739-600  
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br




### Green Pin® Foundry Hook E GR10

#### Grade 10 eye foundry hook



UCFO



- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted blue
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI<sup>®</sup> DGUV

for chain diameter		working load limit	length	diameter eye inside	width opening	thickness	width	diameter eye outside	width outside	length	thickness	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
6	<sup>7</sup> / <sub>32</sub>	1.4	93	18	48	17	22	38	97	124	6	0.33
8	<sup>9</sup> / <sub>32</sub> - <sup>5</sup> / <sub>16</sub>	2.6	124	25	63	22	29	50	129	165	8	0.78
10	<sup>3</sup> / <sub>8</sub>	4	157	33	80	28	36	65	161	208	10	1.5
13	<sup>1</sup> / <sub>2</sub>	6.8	190	44	96	36	46	84	198	256	13	3