



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA

Rua Buri, 149 - Laranjeiras – CAIEIRAS/SP – CEP: 07739-600
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br




Green Pin® Sling Hook CL GR10

Grade 10 clevis sling hook



- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted blue
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI[®] DGUV

UCSC



for chain diameter		working load limit	length	width	width opening	thickness	width	width outside	width outside	length outside	diameter pin	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
6	⁷ / ₃₂	1.4	75	7	26	15	20	28	72	108	8	0.29
	⁹ / ₃₂	1.95	95	9	30	20	24	32	87	136	10	0.58
8	⁵ / ₁₆	2.6	95	9	30	20	24	32	87	136	10	0.58
10	³ / ₈	4	113	12	33	24	29	42	106	164	13	1.11
13	¹ / ₂	6.8	138	15	37	32	39	54	133	208	16	2.12
16	⁵ / ₈	10.3	161	19	44	40	44	68	165	240	20	3.78
20	³ / ₄	16	198	22	61	49	62	82	208	305	24	7.49