




tycan



UCSCT



## LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA

Rua Buri, 149 - Laranjeiras – CAIEIRAS/SP – CEP: 07739-600

11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

### Green Pin Tycan® Sling Hook CL GR10

#### Grade 10 clevis sling hook

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted blue
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI<sup>®</sup>
- **Compatible with:** FCHLIFT; 2.6t, 4t and 6.8t

for chain size	working load limit	length	width	width opening	thickness	width	width outside	width outside	length outside	diameter pin	weight each
mm	t	a	b	c	d	e	f	g	h	i	kg
11x15	2.6	112	17	30	20	24	44	87	158	13	0.73
11x20	4	129	22	33	24	29	57	106	186	16	1.31
13x30	6.8	159	32	37	32	39	74	133	235	20	2.56

In inch

for chain size	working load limit	length	width	width opening	thickness	width	width outside	width outside	length outside	diameter pin	weight each
inch	t	a	b	c	d	e	f	g	h	i	lbs
7/16 X 19/32	2.6	4 12/32	21/32	1 3/16	25/32	15/16	1 3/4	3 7/16	6 7/32	1/2	1.61
7/16 X 25/32	4	5 3/32	7/8	1 5/16	15/16	1 5/32	2 1/4	4 3/16	7 5/16	5/8	2.88
1/2 X 1 3/16	6.8	6 1/4	1 1/4	1 15/32	1 1/4	1 17/32	2 29/32	5 1/4	9 1/4	25/32	5.64