



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA

Rua Buri, 149 - Laranjeiras – CAIEIRAS/SP – CEP: 07739-600
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br




Green Pin® Sling Hook E GR10

Grade 10 eye sling hook



- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted blue
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI[®] DGVU
- **Note:** from 10 t without flat part

UCSO



for chain diameter		working load limit	length	diameter inside eye	width opening	thickness	width	diameter eye outside	width outside	length	width	thickness	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
6	$\frac{7}{32}$	1.4	84	23	26	15	20	43	72	114	10	6	0.28
8	$\frac{9}{32} - \frac{5}{16}$	2.6	103	26	30	20	24	51	87	139	12	8	0.52
10	$\frac{3}{8}$	4	128	35	33	24	29	65	106	172	15	10	1.09
13	$\frac{1}{2}$	6.8	152	41	37	32	39	77	133	209	18	12	1.94
16	$\frac{5}{8}$	10.3	190	52	44	40	44	94	165	255	21	16	3.51
20	$\frac{3}{4}$	16	237	60	61	49	62	115	208	327	28	21	7.1