



## LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA

Rua Buri, 149 - Laranjeiras – CAIEIRAS/SP – CEP: 07739-600

11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br





### Green Pin® Connecting Link GR10

#### Grade 10 connecting link



c  
UMJ



- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted blue
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI<sup>b</sup> DGUV

for chain diameter		working load limit t	diameter	width outside	width inside	length inside	length inside	diameter eye	width inside	weight each kg
mm	inch		a mm	b mm	c mm	d mm	e mm	f mm	g mm	
6	<sup>7</sup> / <sub>32</sub>	1.4	8	42	11	20	52	11	15	0.09
8	<sup>5</sup> / <sub>16</sub>	2.6	9	57	14	20	55	16	19	0.18
10	<sup>3</sup> / <sub>8</sub>	4	12	66	18	23	64	18	23	0.31
13	<sup>1</sup> / <sub>2</sub>	6.8	16	83	21	32	85	24	28	0.68
16	<sup>5</sup> / <sub>8</sub>	10.3	19	103	25	40	105	28	34	1.27
20	<sup>3</sup> / <sub>4</sub>	16	23	122	33	49	128	38	42	2.27