



## Green Pin Tyacan® Connecting Link GR10


### Grade 10 connecting link

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted blue
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI<sup>®</sup>



UMJT

for chain size	working load limit	diameter	width outside	width inside	length inside	length inside	diameter eye	width inside	diameter	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	kg
11x15	2.6	9	57	14	20	55	16	19	13	0.21
11x20	4	12	66	18	23	64	18	23	16	0.36
13x30	6.8	16	83	21	32	85	24	28	20	0.75



### In inch

for chain size	working load limit	diameter	width outside	width inside	length inside	length inside	diameter eye	width inside	diameter	weight each
mm	t	a inch	b inch	c inch	d inch	e inch	f inch	g inch	h inch	lbs
7/16 X 19/32	2.6	11/32	2 1/4	9/16	25/32	2 5/32	5/8	3/4	1/2	0.46
7/16 X 25/32	4	15/32	2 19/32	23/32	29/32	2 17/32	23/32	29/32	5/8	0.79
1/2 X 1 3/16	6.8	5/8	3 9/32	13/16	1 1/4	3 11/32	15/16	1 1/8	25/32	1.65

