




UXLO



## LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA

Rua Buri, 149 - Laranjeiras – CAIEIRAS/SP – CEP: 07739-600

11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

### Green Pin® Self Locking Hook E GR10

#### Grade 10 eye self locking hook

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted blue
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI<sup>b</sup> DGUV

for chain diameter		working load limit	length	diameter inside eye	width opening	thickness	width	width outside	width outside	length	width	thickness	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
6	<sup>7</sup> / <sub>32</sub>	1.4	111	24	32	16	26	47	77	147	11	7	0.51
8	<sup>9</sup> / <sub>32</sub> - <sup>5</sup> / <sub>16</sub>	2.6	134	29	43	23	29	57	92	176	14	7	0.91
10	<sup>3</sup> / <sub>8</sub>	4	168	35	47	32	35	69	111	219	17	10	1.79
13	<sup>1</sup> / <sub>2</sub>	6.8	199	46	61	37	45	87	142	264	20	13	3.36
16	<sup>5</sup> / <sub>8</sub>	10.3	247	59	74	43	56	111	185	328	26	16	7
20	<sup>3</sup> / <sub>4</sub>	16	283	70	90	52	61	126	205	372	28	20	9.22