



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA

Rua Buri, 149 - Laranjeiras – CAIEIRAS/SP – CEP: 07739-600
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br




Green Pin® Sling Hook CL EN 1677-2 GR8

Grade 8 clevis sling hook EN 1677-2



- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard :** EN 1677-2
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI[®] DGUV

CSC



for chain diameter		working load limit	length	width	width opening	thickness	width	width outside	width outside	length outside	diameter pin	weight each
mm	inch											
5	$\frac{3}{16}$	0.8	76	7	26	15	20	28	72	108	6	0.29
6	$\frac{7}{32}$	1.12	75	7	26	15	20	28	72	108	8	0.29
7 - 8	$\frac{1}{4} - \frac{5}{16}$	2	95	9	30	20	24	32	87	136	9	0.58
10	$\frac{3}{8}$	3.2	113	12	33	24	29	42	106	164	13	1.1
13	$\frac{1}{2}$	5.4	138	15	37	32	39	54	133	208	16	2.12
16	$\frac{5}{8}$	8.2	161	19	44	40	44	68	165	240	20	3.67
18 - 20	$\frac{3}{4}$	12.8	198	23	61	49	62	82	208	305	24	7.32
22	$\frac{7}{8}$	15.5	236	25	75	54	65	97	242	350	28	10.63