



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA

Rua Buri, 149 - Laranjeiras – CAIEIRAS/SP – CEP: 07739-600


11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Sling Hook E EN 1677-2 GR8

Grade 8 eye sling hook EN 1677-2



CSO



- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard :** EN 1677-2
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 * MPI^b * DGUV *
- **Note:** from 8.2 t without flat part

for chain diameter		working load limit	length	diameter inside eye	width opening	thickness	width	diameter eye outside	width outside	length outside	width	thickness	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
5-6	$\frac{3}{16} - \frac{7}{32}$	1.12	84	23	26	15	20	43	72	114	10	6	0.28
7 - 8	$\frac{1}{4} - \frac{5}{16}$	2	103	26	30	20	24	51	87	139	12	8	0.56
10	$\frac{3}{8}$	3.2	128	35	33	24	29	65	106	172	15	10	1.09
13	$\frac{1}{2}$	5.4	152	41	37	32	39	77	133	209	18	12	1.98
16	$\frac{5}{8}$	8.2	190	52	44	40	44	94	165	255	21	16	3.55
18 - 20	$\frac{3}{4}$	12.8	237	60	61	49	62	115	208	327	28	21	7.1
22	$\frac{7}{8}$	15.5	280	72	75	54	65	132	242	375	30	23	9.9
26	1	21.6	259	70	73	70	75	144	235	371	37	37	13.3
32	1 $\frac{1}{4}$	32.8	299	66	87	78	89	150	281	430	42	42	21.6

* Excluding sizes 26 mm and 32 mm