



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA

Rua Buri, 149 - Laranjeiras – CAIEIRAS/SP – CEP: 07739-600
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br




Green Pin® Self Locking Hook CL GR8

Grade 8 clevis self locking hook



GKC



- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 MPI^b

for chain diameter		working load limit	length	width	width opening	thickness	width	width outside	width outside	length	diameter pin	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
7 - 8	1/4 - 5/16	2	85	9	32	17	25	32	77	136	9	0.55
10	3/8	3.2	116	12	43	24	29	42	92	168	13	1.02
13	1/2	5.4	153	15	47	32	34	54	111	218	16	2.01
16	5/8	8.2	166	19	62	37	46	66	142	247	20	3.7
18 - 20	3/4	12.8	215	23	74	43	57	80	185	312	24	7.59
22	7/8	15.5	242	25	88	52	62	98	207	353	28	10.3