



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA

Rua Buri, 149 - Laranjeiras – CAIEIRAS/SP – CEP: 07739-600
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br




Green Pin® Self Locking Hook E GR8

Grade 8 eye self locking hook

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 MPI[®]



GKO



for chain diameter		working load limit	length	diameter inside eye	width opening	thickness	width	width outside	width outside	length	width	thickness	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
7 - 8	1/4 - 5/16	2	113	24	32	17	25	48	77	151	13	9	0.53
10	3/8	3.2	134	30	43	24	29	59	92	180	17	10	0.94
13	1/2	5.4	170	39	47	32	34	75	111	225	20	12	1.86
16	5/8	8.2	207	49	61	37	46	93	142	273	22	15	3.49
18 - 20	3/4	12.8	257	60	74	43	57	117	185	341	28	21	7.33
22	7/8	15.5	290	71	88	52	62	133	207	383	31	21	9.91