




XLC



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA

Rua Buri, 149 - Laranjeiras – CAIEIRAS/SP – CEP: 07739-600

11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Self Locking Hook EN 1677-3 CL GR8

Grade 8 clevis self locking hook EN 1677-3

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard :** EN 1677-3
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI^b DGUV

for chain diameter		working load limit	length	width	width opening	thickness	width	width outside	width outside	length	diameter pin	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
5	³ / ₁₆	0.8	92	7	32	16	26	28	77	131	6	0.49
6	⁷ / ₃₂	1.12	92	7	32	16	26	28	77	131	8	0.49
7-8	¹ / ₄ - ⁵ / ₁₆	2	116	9	43	23	29	32	92	161	9	0.91
10	³ / ₈	3.2	143	12	47	32	35	42	111	200	13	1.77
13	¹ / ₂	5.4	167	15	61	37	45	54	142	242	16	3.33
16	⁵ / ₈	8.2	201	19	74	43	56	68	185	293	20	6.75
18 - 20	³ / ₄	12.8	232	23	88	51	63	82	207	341	24	9.57