




XLO



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA

Rua Buri, 149 - Laranjeiras – CAIEIRAS/SP – CEP: 07739-600

11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Self Locking Hook E EN 1677-3 GR8

Grade 8 eye self locking hook EN 1677-3

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard :** EN 1677-3
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MPI^b DGVV
- **Note:** from 12.8 t without flat part

for chain diameter		working load limit	length	diameter inside eye	width opening	thickness	width	width outside	width outside	length	width	thickness	weight each
mm	inch	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
5 - 6	$\frac{3}{16} - \frac{7}{32}$	1.12	111	24	32	16	26	47	77	147	11	7	0.51
7 - 8	$\frac{1}{4} - \frac{5}{16}$	2	134	29	43	23	29	57	92	176	14	7	0.91
10	$\frac{3}{8}$	3.2	168	35	47	32	35	69	111	219	17	10	1.79
13	$\frac{1}{2}$	5.4	199	46	61	37	45	87	142	264	20	13	3.36
16	$\frac{5}{8}$	8.2	247	59	74	43	56	111	185	328	26	16	7
18 - 20	$\frac{3}{4}$	12.8	282	69	88	51	63	126	207	374	28	20	9.22